

DOW CORNING(R) 888 SILICONE JOINT SEALANT

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product Details

Product Name: DOW CORNING(R) 888 SILICONE JOINT SEALANT
Other Name: Silicone Sealant
Company Product Code: 04104518
Proper Shipping Name: Not applicable.
Recommended Use: Sealant

1.2 Company Details

Manufacturer/Supplier: Dow Corning Australia Pty Ltd, ABN 36 008 444 166
Address: Darling Park, Tower 2 Locked Bag 2095
 Level 20, 201 Sussex Street North Ryde NSW 1670
 Sydney NSW 2000
24/7 Emergency Telephone Number: 1300-360-732

2. HAZARD IDENTIFICATION

- 2.1 Hazard Classification:** Non-Hazardous Substance. Non-Dangerous Goods.
2.2 Risk Phrase(s): Not hazardous.
2.3 Safety Phrase(s): Avoid contact with skin and eyes.
 Use only in well-ventilated areas.

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Proportion %</u>
Methylvinyl bis(N-ethylacetamido)silane	87855-59-2	<10
Dimethyl, methyldiethylaminoxysiloxane	68952-53-4	<10
Ingredients determined not to be hazardous to 100%		

4. FIRST AID MEASURES

4.1 First Aid Measures:

Ingestion: Get medical attention.
Eye: Immediately flush with water for 15 minutes. Get medical attention.
Skin: Remove from skin and wash thoroughly with soap and water or waterless cleanser.
 Get medical attention if irritation or other ill effects develop or persist.
Inhalation: Remove to fresh air.

4.2 Medical Attention and Special Treatment Needed:

DOW CORNING(R) 888 SILICONE JOINT SEALANT

First Aid Facilities:	None should be required.
Comments:	Treat according to person's condition and specifics of exposure.
Note to physicians:	Treat Symptomatically. For further information, the Medical Practitioner should contact Dow Corning Australia Pty Ltd.

5. FIRE-FIGHTING MEASURES

5.1 Suitable Extinguishing Media:	On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO ₂), dry chemical or water spray. Water can be used to cool fire exposed containers.
5.2 Unsuitable Extinguishing Media:	None established.
5.3 Hazards From Combustion Products:	None.
5.4 Precautions For Fire Fighters and Special Protective Equipment:	Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool. Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals.
5.5 Hazchem Code:	Not applicable.

6. ACCIDENTAL RELEASE MEASURES

6.1 Emergency Procedures:	Not applicable.
6.2 Methods and Materials for Containment and Clean Up Procedures:	Observe all personal protective equipment recommendations described in this MSDS. If diked material can be pumped, store recovered material in appropriate container. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which laws and regulations are applicable.

7. HANDLING AND STORAGE

7.1 Precautions for Safe Handling:	Use with adequate ventilation. Avoid skin and eye contact. Avoid breathing vapor. Keep container closed. Do not take internally. Exercise good industrial hygiene practice. Wash after handling, especially before eating, drinking or smoking.
7.2 Conditions for Safe Storage:	Use reasonable care and store away from oxidizing materials.

DOW CORNING(R) 888 SILICONE JOINT SEALANT

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Exposure Standards:

<u>Ingredients</u>	<u>Exposure Limits</u>
Methylvinyl bis(N-ethylacetamido)silane	None established. No biological limit allocated.
Dimethyl, methyldiethylaminoxysiloxan e	None established. No biological limit allocated.

8.2 Engineering Controls:

Local Ventilation:	Recommended.
General Ventilation:	Recommended.

8.3 Personal Protective Equipment:

Respiratory:	No respiratory protection should be needed.
Suitable Respirator:	None should be needed.
Hand:	Chemical protective gloves should be worn.
Eye:	Use chemical worker's goggles.
Skin:	Wash at mealtime and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Physical Form:	Paste
9.2 Colour:	Gray
9.3 Odour:	Amine-like odor
9.4 pH:	Not determined.
9.5 Vapour Pressure @ 25°C:	Not determined.
9.6 Vapour Density (air=1):	Not determined.
9.7 Boiling Point:	Not determined.
9.8 Melting Point:	Not determined.
9.9 Solubility in Water:	Not determined.
9.10 Specific Gravity @ 25°C:	1.48
9.11 Flash Point:	100 °C (Closed Cup)
9.12 Upper Flammability Limit:	Not determined.
9.13 Lower Flammability Limit:	Not determined.
9.14 Autoignition Temperature:	Not determined.
9.15 Viscosity:	Not determined.

DOW CORNING(R) 888 SILICONE JOINT SEALANT

The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

10. STABILITY AND REACTIVITY

- 10.1 **Chemical Stability:** Stable.
- 10.2 **Conditions to avoid:** None.
- 10.3 **Incompatible Materials:** Can react with strong oxidising agents.
- 10.4 **Hazardous Decomposition Products:** Carbon oxides and traces of incompletely burned carbon compounds. Metal oxides. Silicon dioxide. Formaldehyde. Nitrogen oxides. Quartz. Sulfur oxides. Chlorine compounds.
- 10.5 **Hazardous Reactions :** Hazardous polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

- 11.1 **Possible Routes of Exposure** Inhalation Skin Contact Ingestion

11.2 **Possible Health Effects:**Acute

- Ingestion:** Low ingestion hazard in normal use.
- Eye:** Direct contact may cause moderate irritation.
- Skin:** May cause mild irritation.
- Inhalation:** Irritates respiratory passages very slightly. Vapor overexposure may cause drowsiness.

Chronic

- Ingestion:** Repeated ingestion or swallowing large amounts may injure internally.
- Skin:** Repeated or prolonged exposure may cause irritation.
- Inhalation:** Prolonged or repeated exposure by inhalation may injure internally.
- Other Health Hazard Information:** No known applicable information.

The above listed potential effects of overexposure are based on actual data, the results of studies performed upon similar compositions, component data, and/or expert review of the products.

12. ECOLOGICAL INFORMATION

12.1 **Environmental Fate and Distribution:**

Solid material, insoluble in water. No adverse effects are predicted.

12.2 **Ecotoxicity:**

DOW CORNING(R) 888 SILICONE JOINT SEALANT

No adverse effects on aquatic organisms are predicted.

Bioaccumulation: No bioaccumulation potential.

12.3 Fate and Effects in Waste Water Treatment Plants:

No adverse effects on bacteria are predicted.

13. DISPOSAL CONSIDERATIONS

13.1 Disposal Method: Dispose of in accordance with local regulations.

13.2 Special Precautions for Landfill or Incineration: None known.

14. TRANSPORT INFORMATION

14.1 UN No.: Not applicable.

14.2 Proper Shipping Name: Not applicable.

14.3 Class: Not applicable.

14.4 Packing Group: Not applicable.

14.5 Hazchem Code: Not applicable.

14.6 Sea transport (IMDG)
Not subject to IMDG code.

14.7 Air Transport (IATA-DGR)
Not subject to IATA regulations.

15. REGULATORY INFORMATION

15.1 SUSDP Poisons Schedule Number: None allocated.

15.2 Prohibition/Licensing Requirements: There are no applicable prohibition or notification/licensing requirements, including for carcinogens under Commonwealth, State or Territory legislation.

15.3 Industrial Chemicals (Notification and Assessment) Act 1989: All ingredients listed or exempt.

15.4 HSNO Approval Code: HSR002670

DOW CORNING(R) 888 SILICONE JOINT SEALANT**15.5 Chemical Inventories:**

TSCA:	All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.
EINECS:	Not determined.
IECSC:	This product contains one or more components that may not be listed on the IECSC inventory, but this component(s) is registered as low volume notification under Dow Corning entity in China. Permission to manufacture or import this product into China is limited to the low volume notification submitter.
HSNO:	All ingredients listed or exempt.
PICCS:	One or more ingredients are not listed or exempt.
DSL:	A chemical substance(s) in the material is not listed DSL but 1) meets the low volume exemption or 2) a New Substance Notification has been filed with Environment Canada. Contact your local Dow Corning Office.
KECL:	Not determined.
ENCS/ISHL:	Not determined.

16. OTHER INFORMATION

Contact Point: Product Safety Specialist - 1300-360-732

Prepared by: Dow Corning Australia Pty Ltd

This MSDS summarises our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this Company. Our responsibility for products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request.

(R) indicates Registered Trademark

www.dowcorning.com